




Series
BT

Bimetal Thermometers

2", 3" or 5" Dial, Dual Scale, ±1% FS Accuracy, External Reset



Series BT Bimetal Thermometers offer accurate, reliable service even in the toughest environments. These corrosion resistant units are constructed from stainless steel and are hermetically sealed to prevent crystal fogging. The bimetal element directly drives pointer, eliminating gears and linkage. An external reset screw allows field calibration and easy-to-read aluminum dial minimizes parallax error. Choose back connection, lower connection or adjustable angle for easy viewing and installation. Adjustable models can be rotated a full 360° and tilted over a 180° arc. NOTE: When using in pressurized applications, use a suitable thermowell. Bimetal thermometers are commonly used to measure water temperature on chillers and boilers.

SPECIFICATIONS

- Wetted Materials:** 304 SS.
- Housing Material:** Series 300SS.
- Lens:** Glass.
- Accuracy:** ±1% full scale.
- Response Time:** ≤ 40 seconds.
- Temperature Limits:** Head: 200°F (93°C); Stem: Not to exceed 50% over-range or 1000°F (538°C) or 800°F (427°C) continuously.
- Process Connection:** 1/4" NPT on 2" dial size; 1/2" NPT on 3" or 5" dial size.
- Stem Diameter:** 1/4" O.D.
- Immersion Depth:** Minimum 2" in liquids, 4" in gas.

TEMPERATURE

Thermometers,
Dial

Model	Dial Size, Stem Length	Temperature Range, °F(°C)	Degree Div., °F(°C)	Model	Dial Size, Stem Length	Temperature Range, °F(°C)	Degree Div., °F(°C)
Back Connection				Adjustable Angle Connection			
BTB22551*	2", 2-1/2"	0/250	2	BTA54010D	5", 4"	0/200 (-20/100)	2 (2)
BTB2405D	2", 4"	0/250 (-20/120)	2 (2)	BTA5405D	5", 4"	0/250 (-20/120)	2 (2)
BTB2409D	2", 4"	200/1000 (100/550)	10 (5)	BTA5407D	5", 4"	50/550 (10/290)	5 (5)
BTB32510D	3", 2-1/2"	0/200 (-20/100)	2 (2)	BTA56010D	5", 6"	0/200 (-20/100)	2 (2)
BTB3255D	3", 2-1/2"	0/250 (-20/120)	2 (2)	BTA5605D	5", 6"	0/250 (-20/120)	2 (2)
BTB3257D	3", 2-1/2"	50/550 (10/290)	5 (5)	BTA5607D	5", 6"	50/550 (10/290)	5 (5)
BTB34010D	3", 4"	0/200 (-20/100)	2 (2)	Lower Connection			
BTB3405D	3", 4"	0/250 (-20/120)	2 (2)	BTC3255D	3", 2.5"	0/250(-20/120)	2 (2)
BTB3407D	3", 4"	50/550 (10/290)	5 (5)				
BTB3605D	3", 6"	0/250 (-20/120)	2 (2)				

*Model offered in Fahrenheit scale only.